



TECHNICAL DATA SHEET

AIMOL ATF Multi

Allround Synthetic Automatic Transmission Oil

DESCRIPTION

AIMOL ATF Multi is a synthetic automatic transmission oil for all automatic gearboxes. Especially developed for American, Japanese and Korean automatic gear boxes. AIMOL ATF Multi can be used easy under all operating temperatures, without unnecessary friction. AIMOL ATF Multi is easy shifting, because of the unique combination of synthetic base oils and state-of-the-art additives.

BENEFITS

- ◆ Excellent oxidation and thermal stability;
- ◆ Outstanding lubrication properties;
- ◆ Easy shifting under all operating temperatures;
- ◆ Long lasting friction characteristics due to high quality friction modifiers.

PERFORMANCE LEVEL

AIMOL ATF Multi meets and exceeds the following performance levels/specifications:

- | | |
|---|---|
| ◆ Allison C-4 | ◆ Caterpillar TO-2 |
| ◆ ZF TE ML 09X- 11B- 14B | ◆ MB 236.1...236.9 |
| ◆ Toyota T-III; T-IV | ◆ Dexron® II and III |
| ◆ Mercon, Mercon V | ◆ Volvo 1161540 and Audi G-055-025-A |
| ◆ Hyundai and Mitsubishi SP, SP- II and III | ◆ ATF LT 71141; BMW LT-2 |
| ◆ MAN 339 type D & F; Z1/V1 & Z2 | ◆ Ford M2C-138CJ, 166H, 202B |
| ◆ Isuzu; Saab 93 165 147 | ◆ JASO M 315 1A; JATCO 3100 PL 085 |
| ◆ ATF 7045E, ATF 1375.4 and LA 2634 | ◆ VW G 052 162 A1 |
| ◆ Nissan Matic D, J and K | ◆ GM 9986195, JWS 3309/ 3314/3324 |
| ◆ Mazda M-III; Idemitsu K7 | ◆ Subaru K0410Y0700 |
| ◆ VOITH G- 1363 – G-607 | ◆ Suitable after warranty period:
Toyota WS and ATF + 3 and ATF +4 |

AVAILABLE SIZES

New drum 205 Litre	Art.#87176623902610
Can 20 Litre	Art.#87176623902627
Can 1 Litre (12x1 Carton)	Art.#87176623902634

TYPICAL FIGURES

Parameter	Test method	ATF Multi
Density at 20 °C kg/m ³	ASTM D1298	844
Flashpoint C.O.C. in °C	ASTM D92	>180
Viscosity at -40 °C in cP	ASTM D97	>180
Viscosity at -30 °C in cSt	ASTM D2983	<20 000
Viscosity at -20 °C in cSt	ASTM D4052	1967.2
Viscosity at 0 °C in cSt	ASTM D4052	827.2
Viscosity at 40 °C in cSt	ASTM D4052	209
Viscosity at 100 °C in cSt	ASTM D445	34
Viscosity at -40 °C in cP	ASTM D445	7.5
Viscosity Index	ASTM D2270	197
Pour point in °C	ASTM D97	-48
Colour	-	Red

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL ATF Multi fluid has no adverse health effects provided it is used as directed.

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.