

Technical data

COPASLIP TJC

Double Duty Drill Collar & Tool Joint Compound

Description

MOLYSLIP COPASLIP TJC is a lead free double-duty drill collar and tool joint compound based on highly refined low sulphur, low pour point mineral oil thickened with a complex soap. The product contains both copper flake and graphite as solid lubricants coupled with high levels of corrosion inhibitors, anti-oxidant and anti-wear additives that make it particularly suitable for use under the most aggressive conditions in corrosive wet/humid, dirty or chemical environments where a high degree of water washout resistance is required.

MOLYSLIP COPASLIP TJC has excellent lubricating and anti-wear properties to reduce friction during assembly preventing 'pick-up', galling and seizure facilitating easier breakout in today's demanding oil field applications. The product has been formulated to exceed the requirements of *API RP 5A3 / ISO 137678:2010

MOLYSLIP COPASLIP TJC is effective over a wide temperature range and is specifically designed to prevent seizure of threaded connections and 'cold welding' of rotary shoulder/drill collar/tool joint connections on oilfield equipment such as drill strings, casings, production tools and tubing etc. The double-duty formulation makes the production suitable for use on casing, tubing and line pipe where rationalisation to one product is desirable.

**API RP 5A3/ISO13678:2010 – "Petroleum and natural gas industries-evaluation and testing of thread compounds for use with casing, tubing, line pipe and drill stem elements".*

Features and benefits

- Lead and zinc free
- Allows consistent joint make-up and breakout
- Highly effective protection against corrosion
- Outstanding resistance to water washout
- Can be applied to cold, damp equipment
- Effective over a wide temperature range

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@moly Slip.co.uk www.moly Slip.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927

Technical data

COPASLIP TJC

Double Duty Drill Collar & Tool Joint Compound

Instructions for use

MOLYSLIP COPASLIP TJC should be used as supplied.

Apply manually by brush to clean, degreased and dry (where possible) tool joint threads and shoulders. For best results apply to both mating surfaces.

Storage

MOLYSLIP COPASLIP TJC should be stored in original, unopened packaging, out of direct sunlight at temperatures between 5°C and 35°C. The most up to date shelf life information for Molyslip products can be found on the certificate of analysis issued at the time of manufacture.

Packaging and product code

Code	Pack
M801520	20kg pail

Technical data

COPASLIP TJC

Double Duty Drill Collar & Tool Joint Compound

Technical data

Property	Test method	Result
Appearance	-	Dark copper coloured grease
NLGI Classification	-	1
Thickener	-	Complex soap
Drop point	IP 396	>250°C
4-ball Weld load	IP 239	620kg
Density (kg/L)	IP 530	1.25
Solids content	-	>40%
Friction factor*	-	1.2
Service rating	-	-20°C to +250°C

Note: These values are typical only and do not constitute a specification

*The Friction Factor is a 'relative' number, many operational variables such as pipe size, thread type / geometry, drilling muds and extraneous contamination, etc. affect the friction factor. In all instances experience and prior application knowledge should be used to adjust make-up torque accordingly. If in doubt, contact the drill pipe manufacturer for torque and friction- related specifications.

Limited warranty information

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. We accept no liability for any loss and/or damage arising from a failure to store our products in accordance with the information contained in this technical sheet.

Metalube Group's sole warranty is that our products will meet their quality control specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

To the fullest extent permitted by applicable law, Metalube Group specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability. Metalube Group disclaims liability for any incidental or consequential damages.

Metalube Group Ltd, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester, M44 5EG, UK

Tel: +44 (0)161 775 7771 enquiries@moly Slip.co.uk www.moly Slip.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927